



Alfa Laval T25

Gasketed plate heat exchanger for a wide range of applications

Introduction

Alfa Laval Industrial line is a wide product range that is used in virtually all types of industry.

Designed for high throughput, this model delivers excellent thermal performance. A large selection of plate and gasket types is available.

Applications

- Biotech and Pharmaceutical
- Chemicals
- Energy and Utilities
- Food, Dairy and Beverages
- Home and Personal care
- HVAC and Refrigeration
- Machinery and Manufacturing
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Semiconductor and Electronics
- Stee
- Water and Waste treatment

Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

Features

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:



- Five-point alignment
- T-bar roller
- CurveFlowTM distribution area
- PowerArcTM plate pattern divider
- ClipGripTM gasket attachment
- Offset gasket groove
- OmegaPortTM noncircular port holes



- · Leak chamber
- FlexFlowTM plate design
- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- · Lock washer
- Tightening bolt cover


Alfa Laval 360° Service Portfolio


Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, integrity testing, monitoring and much more.

For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.

Dimensional drawing

Measurements mm (inches)





Frame	Н	W	h	
FM pvcALS, PED,	0661 (104.0")	010 (05 0")	001 (10 0")	
Marine ¹	2661 (104.8")	913 (35.9")	331 (13.0")	
FG pvcALS, ASME,	2661 (104.8")	913 (35.9")	331 (13.0")	
PED	2001 (104.6)	913 (33.9)	331 (13.0)	
FD pvcALS, PED	2711 (106.7")	913 (35.9")	331 (13.0")	
FD ASME	2711 (106.7")	942 (37.1")	331 (13.0")	
FS pvcALS	2711 (106.7")	913 (35.9")	331 (13.0")	
FS ASME	2711 (106.7")	942 (37.1")	331 (13.0")	

 $^{^{1}}$ Marine includes the pressure vessel codes: ABS, BV, CCS, ClassNK, DNV, KR, LR, RINA, and RMRS.

The number of tightening bolts may vary depending on pressure rating.

Technical data

Plates	Туре	Free channel, mm (inches)	
В	Single plate	2.00 (0.079)	
Р	Single plate	2.90 (0.114)	
М	Single plate	3.82 (0.15)	

Materials		
Heat transfer	304/304L, 316/316L, 254, C276, TiPd	
plates	Ti	
Field gaskets	NBR, EPDM, FKM, HNBR	
Flange	Metal lined: stainless steel, Alloy 254, Alloy C276, titanium	
connections	Rubber lined: NBR, EPDM	
Frame and	Carbon steel, epoxy painted	
pressure plate	Carbon Steel, epoxy painted	

Other materials may be available on request.

Operational data

		Max. design
Frame type	Max. design pressure barg (psig)	temperature °C
		(°F)
FM, PED	11.5 (188)	180 (356)
FM, pvcALS	10.3 (150)	180 (356)
FM, Marine ¹	10.0 (145)	100 (212)
FG, pvcALS	16.0 (232)	180 (356)
FG, ASME	10.4 (151)	250 (482)
FG, PED	16.0 (232)	150 (302)
FD, pvcALS	25.0 (362)	180 (356)
FD, ASME	20.7 (300)	250 (482)
FD, PED	25.0 (362)	180 (356)
FS, pvcALS	30.0 (434)	180 (356)
FS, ASME	27.6 (400)	250 (482)

¹ Marine includes the standards: ABS, BV, CCS, ClassNK, DNV, KR, LR, RINA, and RMRS.

Extended pressure and temperature rating may be available on request.

Connections

General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable



HydroThrift Corporation

1301 Sanders Ave SW

Massillon, OH 44647 USA

sales@hydrothrift.com 330-837-5141

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval AB (publ) or any of its affiliates (jointly "Alfa Laval"). No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

200000069-15-EN-GB © Alfa Laval AB